

FEATURES

- | Bi-directional
- | Halogen-free
- | Low slope resistance
- | Very low clamping voltage
- | Sharp breakdown voltage
- | Symmetric in leads width for easier soldering during assembly
- | Glass passivated junction
- | Ultra compact: less than one-tenth the size of traditional discrete solutions
- | IEC-61000-4-2 ESD 15KV(Air), 8KV(Contact)



AK3

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Storage Temperature Range	T_{STG}	-55~150	$^{\circ}\text{C}$
Operating junction Temperature Range	T_J	-55~125	$^{\circ}\text{C}$
Current Rating	I_{PP}	3	KA

Notes:
 Rated I_{pp} measured with 8/20 μs pluse

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Part Number	Device Marking Code	Reverse Stand-off Voltage	Breakdown Voltage V _{BR} @I _T		Test Current I _T	Maximum Clamping Voltage @I _{PP}	Peak Pulse Current	Reverse Leakage @V _{RWM}
		V _{RWM} (V)	Min(V)	Max(V)	(mA)	V _C (V)	I _{PP} (A)	I _R (μA)
AK3-015C	3-015C	15	16	19	10	28	3000	10
AK3-020C	3-020C	20	22	24	10	50	3000	10
AK3-025C	3-025C	25	28	30	10	60	3000	10
AK3-030C	3-030C	30	32	37	10	80	3000	10
AK3-042C	3-042C	42	47	51	10	105	3000	10
AK3-058C	3-058C	58	64	70	10	110	3000	10
AK3-066C	3-066C	66	72	80	10	120	3000	10
AK3-076C	3-076C	76	85	95	10	140	3000	10
AK3-100C	3-100C	100	110	122	10	165	3000	10
AK3-133C	3-133C	133	147	162	10	220	3000	10
AK3-150C	3-150C	150	158	194	10	230	3000	10
AK3-170C	3-170C	170	179	220	10	260	3000	10
AK3-190C	3-190C	190	200	245	10	290	3000	10
AK3-208C	3-208C	208	223	246	10	305	3000	10
AK3-240C	3-240C	240	250	285	10	340	3000	10
AK3-275C	3-275C	275	300	335	10	435	3000	10
AK3-300C	3-300C	300	330	366	10	470	3000	10
AK3-380C	3-380C	380	401	443	10	520	3000	10
AK3-430C	3-430C	430	440	490	10	625	3000	10

CHARACTERISTIC CURVES

Fig.1 V-I Curve characteristics




Fig.2 Pulse derating Curve




Fig.3 Pulse Waveform






Fig.4 Typical V_{BR} Vs Junction Temperature




WAVE SOLDERING



Wave Parameter		Lead-free assembly
Pre Heat	Temperature Min	100°C
	Temperature Max	150°C
	Time(min to max)	60 – 180 secs
Solder pot Temperature		280°C Max
Solder Dwell Time		2-5 seconds

AK3 PACKAGE INFORMATION



Ref.		Millimeters		Inches	
		Min.	Max.	Min.	Max.
A		23.15	25.15	0.911	0.990
B		2.30	3.00	0.091	0.118
C		5.00	20.0	0.197	0.787
D		14.0Max		0.551Max	
E		1.20	1.40	0.047	0.055
F		14.0Max		0.551Max	
G-	15C-25C	4.00Max		0.157Max	
	30C-42C	5.00Max		0.197Max	
	58C-76C	6.00Max		0.236Max	
	100C-133C	8.00Max		0.315Max	
	170C-190C	10.0Max		0.394Max	
	240C-300C	14.0Max		0.551Max	
	380C-430C	17.0Max		0.670Max	
L1/L2		L1=L2 tolerance±0.047inch±(1.20mm)			

ORDERING INFORMATION

Part Number	Component Package	QTY	Packaging Option
AK3	AK3	84pcs/Box	Bulk

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware' s global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.