

FEATURES


- | High Density Cell Design For Low $R_{DS(On)}$
- | Voltage Controlled Small Signal Switch
- | Rugged and Reliable
- | High Saturation Current Capability
- | Lead free product is acquired

APPLICATION

- | Direct logic-level interface: TTL/CMOS
- | Drivers: relays, solenoids, lamps
- | hammers, display, memories, etc.
- | Battery operated systems
- | Solid-state relays

APPROVALS


RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003



SOT-23



Marking



Schematic Symbol

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	2.3	A
Continuous Source-Drain Current(Diode Conduction)	I_S	0.6	A
Power Dissipation	P_D	0.35	W
Operating Junction	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to 150	$^{\circ}\text{C}$
Thermal Resistance from Junction to Ambient ($t \leq 5s$)	$R_{\theta JA}$	357	$^{\circ}\text{C/W}$

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Drain-source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =10μA	20			V
Gate-source leakage ^a	I _{GSS}	V _{DS} =0V, V _{GS} =±12V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} =20V, V _{GS} =0V			1	uA
Gate-source threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	0.4	0.7	1.0	V
Drain-source on–state resistance ^a	R _{DS(on)}	V _{GS} =4.5V, I _D =2.5A		0.055	0.085	Ω
		V _{GS} =2.5V, I _D =2.1A		0.070	0.125	Ω
Diode forward voltage ^a	V _{SD}	I _S =0.94A, V _{GS} =0V		0.76	1.2	V
Dynamic						
Input capacitance ^b	C _{iss}	V _{DS} =10V, V _{GS} =0V, f=1MHz		300		pF
Output capacitance ^b	C _{oss}			120		pF
Reverse transfer capacitance ^b	C _{rss}			80		pF
Total gate charge	Q _g	V _{DS} =10V, V _{GS} =4.5V, I _D =2.5A		4.0	10	nC
Gate-source charge	Q _{gS}			0.65		nC
Gate-drain charge	Q _{gD}			1.5		nC
Switching ^b						
Turn-on delay time	t _{d(on)}	V _{DD} =10V, V _{GEN} =4.5V I _D =2.5A, R _G =6Ω, R _L =5.5Ω		7	15	ns
Rise Time	t _r			55	80	ns
Turn-Off Delay Time	t _{d(off)}			16	60	ns
Fall yime	t _f			10	25	ns

Notes:

a. Pulse Test:Pulse Width≤300μs,Duty Cycle≤2%.

b. These parameters have no way to verify.

PARAMETER CHARACTERISTIC CURVE

Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: $R_{DS(ON)} - I_D$






Figure 4: $R_{DS(ON)} - V_{GS}$




SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




SOT-23 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.80	3.05	0.110	0.120
B	1.20	1.40	0.047	0.055
C	0.90	1.15	0.035	0.045
D	0.37	0.50	0.015	0.020
G	1.75	2.05	0.069	0.081
H	0.01	0.100	0.001	0.004
J	0.085	0.180	0.003	0.007
K	0.35	0.69	0.014	0.029
L	0.89	1.02	0.035	0.040
S	2.10	2.65	0.083	0.104
V	0.45	0.60	0.018	0.024

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.71	0.97	0.028	0.038
B	1.88	2.13	0.074	0.084
C	0.71	0.97	0.028	0.038
D	0.81	1.07	0.032	0.042

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
SNM2302	SOT-23	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.